

Modell

	Fullrange Monitor	Subwoofer	nearfield	midfield	Main	Hörabstand	FIRTEC	DMC	NEXT	coaxial point source	digital Input	remoteable	amplifier	Leistung pro Weg
c5	x	x				> 0.5 m							MOSFET	70/170W
c55	x	x	x			> 0.5 m							MOSFET	80/180/180W
c8	x	x	x			> 0.5 m							MOSFET	80/180W
c88	x	x	x	x		> 0.5 m							MOSFET	80/180/180W
d60	x	x				> 0.5 m	x		x			x	PWM	280W each way
d606	x	x	x			> 0.6 m	x		x			x	PWM	280W each way
d80	x	x	x			> 0.5 m	x		x			x	PWM	280W each way
d808	x	x	x	x		> 0.8 m	x		x			x	PWM	280W each way
c120	x			x	x	> 1.0 m	x		x	x		x	PWM	280W each way
cb120		x				--							MOSFET	400W
cb150		x				--							MOSFET	400w
adm25	x	x	x	x		> 0.5 m	x			x		x	PWM	280W each way
adm22	x			x	x	> 1.0 m	x			x		x	PWM	280W each way
a200	x			x	x	> 1.0 m	x			x		x	PWM	280W each way
a300	x			x	x	> 1.5 m	x			x		x	PWM	280W each way
adm15	x				x	> 1.5 m	x			x		x	MOSFET / bass driver PWM	100/200/400W
adm10	x			x	x	> 1.5 m	x			x		x	MOSFET / bass driver PWM	150/200/400W
linemaster	x				x	> 1.5 m	x	x	x		x	x	MOSFET	100/200/400W
admb2		x				--							MOSFET	200W
admb3		x				--							MOSFET	200W
amdwo		x				--							MOSFET	400W

NEXT

DMC

FIRTEC

FIRTEC

FIRTEC